

## 3325

## Medium Light



**Compact / Safety Certified / Tail Switch Design** - All three are combined in the 3325 LED flashlight

The compact and lightweight design begins with the use of only 3 AA alkaline batteries and yet produces over 162 lumens of brilliant light. Safety certified for use in most volatile work environments. The rear mounted switch make the 3325 a perfect match for any helmet mounted applications. The photoluminescent ("glow in the dark") shroud ensures you'll be able to locate your light even in the darkest of conditions. For added reliability, an IPX7 ingress protection level will protect the 3325 in the most severe weather conditions. Backed by Pelican's Lifetime Guarantee makes the 3325 a true value!

- Safety Certified Class I, Division I
- Tail switch for easy one-handed operation
- Glow-in-the-dark shroud
- 3 AA Batteries (Included)
- Ingress Protected IPX7
- Pelican's Lifetime Guarantee

#### **CONFIGURATIONS**

3325 - Standard

#### **DIMENSIONS**

Length: 6.06"

#### **MATERIALS**

Body: EXL O-Ring: EPDM

Lens: Polycarbonate (PC)

**Shroud**: Photo luminescent Polycarbonate (PC)

#### COLORS



# LIGHT SPECS

Lamp Type: LED

FL1 STANDARD	HIGH
314	162 LUMENS
$\Theta$	16h 0mins
	144m
	5215cd
The	IPX7

# POWER

Battery Size: AA
Battery Type: Alkaline
Battery Quantity: 3
Batteries Included: yes

**Volts**: 4.5v

#### WEIGHT

Weight With Batteries: 6.1 oz Weight Without Batteries: 3.6 oz

## **SWITCH**

**Switch Type**: Push Button **Light Modes**: On / Off

## **CERTIFICATIONS**

Class I, Division 1 IECEx ia

# OTHER

Minimum Pack: 1 Package Code: C

#### Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 <u>sales@pelican.com</u> • <u>www.pelican.com</u>