9480

Remote Area Lighting System

- Up to 4,000 lumens (calculated)
- Up to 28 hrs of run time
- 3 pre-set light output levels
- Maintenance free LED array with 50,000 hour life expectancy
- Built Pelican tough
- Full time battery level indication with low level flashing indicator
- Deployable mast with 340 degree rotation
- Multiple deployment positions
- Convenient shoulder strap
- Quick release / Hot swappable battery design with 12 volt power supply
- Free Bluetooth iPhone™ App Controls Multiple Units

CONFIGURATIONS

9480 - Standard

DIMENSIONS

Head (L x W x D): 8.25 x 5.75" x 2.25 (21 x 14.6 x 5.7 cm)
Closed (L x W x D): 15.50 x 6.50" x 10.25 (39.4 x 16.5 x 26 cm)
Mast Length: 23.75"

MATERIALS

Body: Polypropylene
Head: Aluminum
Mast: Aluminum
Lens: Polycarbonate (PC)

COLORS


Black

Yellow

LIGHT SPECS

Lumens (High): 4000
Lumens (Med): 3000
Lumens (Low): 1000
Lamp Heads: 1
Lamp Type: LED
Number of LEDs: 8
Lamp Life: 50000 hrs
Beam Spread: 125°
IP Rating: 54

POWER

Run Time (High): 6.00 hrs
Run Time (Med): 8.00 hrs
Run Time (Low): 28.00 hrs
Battery Type: Sealed Lead Acid (SLA)
Battery Lifespan: 500 cycles
Charge Time: 480 mins
Battery Level Indicator: Full-time battery level display and low battery warning (visible flashing)
Sockets (Primary): 1
Volts: 12.0v

WEIGHT

Weight: 27.50 lbs

SWITCH

Switch Type: Silicone Rubber Keypad
Light Modes: High / Medium / Low / Flashing

Pelican Products, Inc.
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com