1150

Small Case

- **Watertight, crushproof, and dustproof**
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence

CONFIGURATIONS

1150 - Standard
1150NF - With No Foam

DIMENSIONS

Interior (L x W x D): 8.29 x 5.79" x 3.75 (21.1 x 14.7 x 9.5 cm)
Exterior (L x W x D): 9.44 x 7.80" x 4.29 (24 x 19.8 x 10.9 cm)
Lid Depth: 0.75"
Bottom Depth: 2.87"
Total Depth: 3.62"
Int Volume: 0.1 ft³

MATERIALS

Body: Polypropylene
Latch: Polypropylene
O-Ring: Polymer
Pins: Stainless Steel
Foam: 1.3 lb Polyurethane
Purge Body: ABS
Purge Vent: 3 Micron Hydrophobic Non-Woven
Purge O-Ring: 70 Shore Nitrile

COLORS

Black | Silver | Orange | Yellow | Blue | OD Green | Desert Tan

WEIGHT

Weight With Foam: 1.75 lbs
Weight Without Foam: 1.61 lbs
Buoyancy: 8.00 lbs
Master Pack Weight: 13.95 lbs

TEMPERATURE

Minimum Temperature: -40°
Maximum Temperature: 210°

CERTIFICATIONS

IP67
Def Stan 81-41
STANAG 4280

FOAM PROPERTIES

Layer 1 (Lid): 0.74" Convolute
Layer 2 (Base): 0.50" Pad
Layer 3 (Base): 2.53" Pick N Pluck

OTHER

Master Pack: 6
Military: yes

Pelican Products, Inc.
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com