AL3232-1412

Trunk

Hinged Lid

- Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact
- Reinforced corners and edges for additional impact protection
- Recessed hardware for extra protection
- Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware
- Molded-in ribs and corrugations for secure, non-slip stacking, columnar strength, and added protection
- Patented molded-in metal inserts for catch and hinge attachment points, which provide strength and spread loads to the container
- One-piece construction, molded from lightweight, high-impact polyethylene

CONFIGURATIONS

AL3232-1412 - Standard

DIMENSIONS

Interior (L x W x D): 32.43 x 32.43" x 26.75 (82.4 x 82.4 x 67.9 cm)
Exterior (L x W x D): 35.43 x 35.43" x 30.44 (90 x 90 x 77.3 cm)
Lid Depth: 12.25"
Bottom Depth: 14.50"
Total Depth: 26.75"
Int Volume: 16.28 ft³

MATERIALS

Body: RotoMolded Polyethylene
Latch: Steel (Nickel-black Plated)
O-Ring: Silicone Sponge
Pins: Stainless Steel
Pins (Alt): Aluminum
Purge Body: Aluminum

COLORS



Black

WEIGHT

Weight: 68.40 lbs
Buoyancy: 1312.16 lbs
Master Pack Weight: 70.40 lbs

TEMPERATURE

Minimum Temperature: -20°
Maximum Temperature: 140°

OTHER

Military: yes

Pelican Products, Inc.
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com