PELICAN™

iM2950

Large Case

Travel Case

- Five Press & Pull Latches
- Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

CONFIGURATIONS

iM2950 - Standard
iM2950-X0000 - With No Foam
iM2950-X0002 - With With Padded Dividers

DIMENSIONS

Interior (L x W x D): 29.00 x 18.00" x 10.50 (73.7 x 45.7 x 26.7 cm)
Exterior (L x W x D): 31.30 x 20.40" x 12.20 (79.5 x 51.8 x 31 cm)
Lid Depth: 2.00"
Bottom Depth: 8.50"
Total Depth: 10.5"
Int Volume: 3.17 ft³

MATERIALS

Body: Injection Molded HPX® high performance resin
Latch: Valox - Polybutylene Terephthalate (PBT)
Latch (Alt): Xenoy - Polyester/Polycarbonate blend
O-Ring: Silicone Sponge
Pins: Stainless Steel
Pins (Alt): Aluminum
Foam: 1.3/1.35 polyester
Purge Body: Valox - Polybutylene Terephthalate (PBT)
Purge Body (Alt): Xenoy - Polyester/Polycarbonate blend
Purge Vent: Gortex membrane
Purge O-Ring: Buna-N, 50-60 Durometer Shore A

COLORS

Black

Yellow

OD Green

WEIGHT

Weight With Foam: 28.70 lbs
Weight Without Foam: 0020.80 lbs
Buoyancy: 200.85 lbs
Master Pack Weight: 28.00 lbs

TEMPERATURE

Minimum Temperature: -20°
Maximum Temperature: 140°

CERTIFICATIONS

MIL-STD-810F
ATA 300
FED-STD-101C

FOAM PROPERTIES

Layer 1 (Lid): 2.00" Convolute
Layer 2 (Base): 0.63" Pad
Layer 3 (Base): 2.00" Pick N Pluck
Layer 4 (Base): 2.00" Pick N Pluck
Layer 5 (Base): 2.00" Pick N Pluck
Layer 6 (Base): 2.00" Pick N Pluck

OTHER

Extendable Handle: yes
Master Pack: 1
Military: yes

Pelican Products, Inc.
23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
sales@pelican.com • www.pelican.com